



Product Serie: Baker Artikelnummer: 861811563

The GRAM BAKER M 1808 CBG A DLB DRB L2 is a with a net internal volume of 297 Ltr.

Generations of bakeries, confectioners, and patisseries are trusting GRAM BAKER storage and process cabinets to accommodate their bakery products. The GRAM air circulation system is key to maintain correct and uniform temperature and humidity levels inside the cabinet. The air is exhausted and refrigerated before being directed back into the cabinet, circulating around all food items. Thus, unwanted dehydration and skin forming of doughs can be avoided almost entirely.



Both storage and process cabinets come with built-in functionalities that preserve the quality of your bakery products at all times.

### Low Running Costs

The energy-efficient refrigeration technology implemented in this wide line-up of storage cabinets can help saving running costs on a day-to-day basis.

### **Built-in Safety**

All BAKER Cabinets come with a controller equipped with safety functions: Door alarm, alarms for high-temperature levels, or when the cleaning of the condenser filter is required to avoid overheating. A top panel perfectly protects the controller from water splashes.

### Multi-Functional

The SF can be used as a quick chiller/freezer, storage freezer, storage refrigerator, or thawing cabinet. If required, the GA can be also used continuously as a freezer, as a refrigerator, or as a prover.

## Designed for Bakers

The GRAM BAKER series strikes with features, specifically designed for the requirements of bakery businesses. The cabinet meets standard bakery tray sizes and the support rails can be individually positioned.

- Right-hand hinged door with lock
- Air circulation system
- Dry cooling and controlled thawing (M versions)
- Automatic defrost and reevaporation of water

# **SPECIFICATIES**

Temperatuurbereik	-5/+12°C
Inhoud, bruto (liter)	588
Netto bruikbaar volume (liter)	297
Inwendig	RvS
Afmetingen W x D x H (mm)	1700 x 800 x 885/950
Gewicht, verpakt (kg)	184
Koelmiddel	R290
GWP	3
Aansluiting	230V, 50 Hz
Aansluitwaarde (Watt)	389
Energie verbruik Ecodesign (kWh)	1990

Energie Efficiëntieklasse	E
Energie Efficiëntie Index EEI	78.1
Isolatie (mm)	50 mm (cyclopentaan)
Koelcapaciteit bij -10°C (Watt)	386
GN - Shelf size	Plaatmaat 40 x 60 cm
Deur type	Geïsoleerde deur
Poten / Wielset	H = 135/200 mm (L2)
Uitwendig	RvS
Koelmiddel (kg)	0.07
CO2 Equivalent (kg)	0.23
Uitgerust met	Stainless steel solid top, 2 door sections each with 9 pairs of adjustable supports (60 x 40 cm)